

















Modular Timers

TEMSA Programmable Asymmetrical Timer		TEMS Multi-Scale Timer		TEMFS Multi-Function Timer		Timer Functions	
						         	
DE		A		A-J			
Features							
<ul style="list-style-type: none"> - Compact size - 1 Module (17.5 mm) - Output relay 1 pole changeover contact - DIN rail mounting - Time range 0.2sec - 100hr - 10 Time scales selectable - Universal power supply 24-110VDC / 24-240VAC 		<ul style="list-style-type: none"> - Compact size - 1 Module (17.5 mm) - Output relay 1 pole changeover contact - DIN rail mounting - Multi-scale - Universal power supply 24-110VDC / 24-240VAC 		<ul style="list-style-type: none"> - Compact size - 1 Module (17.5 mm) - Output relay 1 pole changeover contact - DIN rail mounting - 10 functions selectable - Time range 0.1 sec - 10days - Universal power supply 24-110VDC / 24-240VAC 			
Wiring Diagrams							
							
Technical Specifications							
INPUT Power supply voltage DC: 24-110VDC Power supply voltage AC: 24-240VAC Power consumption (max AC): VA: 8.5 (2.6W)		INPUT Power supply voltage DC: 24-110VDC Power supply voltage AC: 24-240VAC Power consumption (max AC): VA: 8.5 (2.6W)		INPUT Power supply voltage DC: 24-110VDC Power supply voltage AC: 24-240VAC Power consumption (max AC): VA: 8.5 (2.6W)			
OUTPUT RELAY Rated current: 8A Rated operational voltage: 250VAC / 24VDC Changeover contact: 1 Au+AgCdO		OUTPUT RELAY Rated current: 8A Rated operational voltage: 250VAC / 24VDC Changeover contact: 1 Au+AgCdO		OUTPUT RELAY Rated current: 8A Rated operational voltage: 250VAC / 24VDC Changeover contact: 1 Au+AgCdO			
GENERAL FEATURES Time range rotary switch: 0.2s-100h Operating temperature: -10/+50°C Storage temperature: -30/+70°C Isolation voltage: 4kV Protection degree: IP40 Relative humidity: 95RH% Weight: 65g Dimensions: 98 x 17.5 x 64 mm		GENERAL FEATURES Time range rotary switch: 0.1s-10days Operating temperature: -10/+50°C Storage temperature: -30/+70°C Isolation voltage: 4kV Protection degree: IP40 Relative humidity: 95RH% Weight: 60g Dimensions: 98 x 17.5 x 64 mm		GENERAL FEATURES Time range rotary switch: 0.1s-10days Operating temperature: -10/+50°C Storage temperature: -30/+70°C Isolation voltage: 4kV Protection degree: IP40 Relative humidity: 95RH% Weight: 65g Dimensions: 98 x 17.5 x 64 mm			
PART NUMBER	TRADE PRICE	PART NUMBER	TRADE PRICE	PART NUMBER	TRADE PRICE		
TEMSA		TEMS		TEMFS			