

**JOINON**  
CHARGE YOUR LIFE

**INVESTING IN  
OUR FUTURE  
STARTS TODAY**



## I-CON EV CHARGING STATIONS

7.4kW Single Phase, 11kW & 22kW Three Phase Models



The I-CON range is perfect for domestic use. They ensure fast, safe and reliable charging of any vehicle. A cost effective EV charger made in Italy.

- AUTOSTART type 2 charging points are automatic with the connection of the electric vehicle by any user without authentication. A straight forward and simple system, without providing a user management and control system.
- Optional RFID equipped charging stations are ideal for ensuring reserved access to charging points and feature a touch screen interface with energy metering built in. RFID cards act as keys to activate the charging process, perfect for apartments and commercial use.




### Various Mounting Options



**WALLBOX  
WALL MOUNTED**



**WALLBOX  
FLUSH-MOUNTING**



**WALLBOX FLOOR-MOUNTED  
WITH SUPPORT**



## DC Leakage Protection built in


I-CON chargers are equipped with DC leakage protective devices (RDC-DD) as a standard, according to NZ regulations.



Charge with one hand  
- Simple "one hand"  
socket design means  
user can easily plug in  
and recharge vehicles.



Key switch load management manual selector allows  
user to partialise the charging power to suit the over  
all power usage load across the building.



### TECHNICAL CHARACTERISTICS

CODE	GWJ 3012 A	GWJ 3013 A	GWJ 3014 A	GWJ 3214 R
Charging mode (EN 61851)	Mode 3	Mode 3	Mode 3	Mode 3
Charging socket (EN 62196)	Type 2	Type 2	Type 2	Type 2
Connector type	Mobile connector	Mobile connector	Mobile connector	Mobile connector
Cable Length (if available)	5 meters	5 meters	5 meters	5 meters
ELECTRICAL RATING				
Power terminal block	3 x 10 mm²	3 x 10 mm²	5 x 10 mm²	5 x 10 mm²
Rated voltage	230V Single Phase	400V Three Phase	400V Three Phase	400V Three Phase
Maximum Current	32A	16A	32A	32A
Maximum power	7.4 kW	11 kW	22 kW	22 kW
User protection	DC Leak 6mA	DC Leak 6mA	DC Leak 6mA	DC Leak 6mA
Energy measurement	-	-	-	Meter MID
Connectivity	-	-	-	BLE (Setup app)
Load management	Manual selector *	Manual selector *	Manual selector *	-
Charging activation	FREE	FREE	FREE	RFID
Human Interface	LED	LED	LED	Display + Slider touch
MECHANICAL PROPERTIES				
Installation type	Wall-mounted (or floor with support)			
Material	Post-Industrial source thermoplastic			
IP protection	IP55			
Impact protection	IK10			
Operating temperature	-25°C / +50°C			
Available accessories				
Single-side floor support	GWJ 8102			
RFID card	GWJ 8001			

(\*) the selector allows to partialize the charging power: 100% - 60% - 30%.

### LED Charging Indicator Light

CP ready to use


Charging session

Error

The I-CON Chargers  
are equipped with a  
type 2 lead and plug.

Built tough IK10  
impact protection  
rated

### OVERALL DIMENSIONS



**E.I.C.** Electrical  
Importing  
Company

QUALITY ELECTRICAL COMPONENTS FOR INDUSTRY

Electrical Importing Company Limited

(09) 634 2978 | www.eic.nz | sales@eic.nz

117A Captain Springs Rd, Onehunga,  
Auckland 1061

PO Box 13 872, Auckland 1643, NZ