



### Basic features

Approval/Conformity	CE UKCA WEEE
Basic standard	IEC 60947-5-2

### Display/Operation

Function indicator	yes
Power indicator	no

### Electrical connection

Connection	M12x1-Male, 4-pin, A-coded
Polarity reversal protected	yes
Protection against device mix-ups	yes
Short-circuit protection	yes

### Electrical data

Load capacitance max. at Ue	1 µF
Min. operating current I <sub>m</sub>	0 mA
No-load current I <sub>o</sub> max., damped	15 mA
No-load current I <sub>o</sub> max., undamped	10 mA
Operating voltage U <sub>b</sub>	10...55 VDC
Output resistance R <sub>a</sub>	33.0 kΩ + D/33.0 kΩ + D
Protection class	II
Rated insulation voltage U <sub>i</sub>	250 V AC
Rated operating current I <sub>e</sub>	200 mA
Rated operating voltage U <sub>e</sub> DC	24 V
Rated short circuit current	100 A
Ready delay t <sub>v</sub> max.	10 ms
Residual current I <sub>r</sub> max.	80 µA
Ripple max. (% of U <sub>e</sub> )	15 %
Switching frequency	150 Hz
Utilization category	DC -13
Voltage drop static max.	2.5 V

### Environmental conditions

Ambient temperature	-25...70 °C
Contamination scale	3
EN 60068-2-27, Shock	Half-sinus, 30 g <sub>n</sub> , 11 ms
EN 60068-2-6, Vibration	55 Hz, amplitude 1 mm, 3x30 min
IP rating	IP68

### Functional safety

MTTF (40 °C)	500 a
--------------	-------

## Interface

<b>Switching output</b>	PNP normally open/normally closed (NO/NC)
-------------------------	---

## Material

<b>Housing material</b>	Brass, Nickel-free coated
<b>Material sensing surface</b>	PA 12

## Mechanical data

<b>Dimension</b>	Ø 30 x 83 mm
<b>Installation</b>	for flush mounting
<b>Mounting length</b>	50.00 mm
<b>Size</b>	M30x1.5
<b>Tightening torque</b>	70 Nm

## Range/Distance

<b>Assured operating distance Sa</b>	12 mm
<b>Hysteresis H max. (% of Sr)</b>	15.0 %
<b>Rated operating distance Sn</b>	15 mm
<b>Real switching distance sr</b>	15 mm
<b>Repeat accuracy max. (% of Sr)</b>	5.0 %
<b>Switching distance marking</b>	■ ■
<b>Temperature drift max. (% of Sr)</b>	10 %
<b>Tolerance Sr</b>	±10 %

## Remarks

The sensor is functional again after the overload has been eliminated.  
 Flush: See installation instructions for inductive sensors with extended range 825357.  
 For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

## Connector Drawings



## Wiring Diagrams

