



Direct-On-Line (DOL) Starters

- In Plastic Enclosure IP65

Design

- Shock-proof plastic, self extinguishing material
- Ingress Protection Rating: IP65
- Dimensions: H203 x W95 x D120mm
- Entry: 4x 20mm holes

Ordering Information

<p>GHDOL - B - 23 - 9 - 400</p> <p>DOL Starter</p> <p>Contactor Size B, C or D (Max Power)</p> <p>Overload Type RTD23E^① (or RTD32E^②)</p> <p>Overload Rating (Max Amps^③ -see rating table)</p> <p>Coil Voltage (24, 48, 110, 230, or 400 Vac)</p>		
MAX POWER	PART NUMBER ^①	TRADE PRICE ^③
4 kW	GHDOL-B-23-__-__	
5.5 kW	GHDOL-C-23-__-__	
7.5 kW	GHDOL-D-23-__-__	



Max Amps (Overload Rating)

CURRENT RANGE	MAX AMPS	TYPE RTD23E ^①	TYPE RTD32 ^②
0.4 ~ 0.6A	0.6	RTD23E-0.6	RTD32-0.6
0.6 ~ 0.9A	0.9	RTD23E-0.9	RTD32-0.9
0.8 ~ 1.2A	1.2	RTD23E-1.2	RTD32-1.2
1.2 ~ 1.8A	1.8	RTD23E-1.8	RTD32-1.8
1.8 ~ 2.7A	2.7	RTD23E-2.7	RTD32-2.7
2.7 ~ 4A	4	RTD23E-4	RTD32-4
4 ~ 6A	6	RTD23E-6	RTD32-6
6 ~ 9A	9	RTD23E-9	RTD32-9
8 ~ 11A	11	RTD23E-11	RTD32-11
10 ~ 14A	14	RTD23E-14	RTD32-14
13 ~ 18A	18	RTD23E-18	RTD32-18

Notes: ^① GHDOL-B-23-__-__ starters include the RTD23E overload relay fitted as standard.
^② Select "Max Amps" from Overload Rating Table.
^③ Trade Prices are for starters fitted with the standard RTD23E overload relay. Starters with the RTD32 overload relay are available on request - POA.