

# 40 CD Range

## Surface-mounting distribution boards and enclosures



4 families capable of offering various solutions in industrial, commercial and domestic sectors.

- High modularity: from 2 to 72 modules;
  - Wide performance range: from IP40 to IP65;
  - Extractable frame versions;
  - Halogen-free material versions;
- IMQ label products.

# 40 CD RANGE

SURFACE-MOUNTING DISTRIBUTION BOARDS AND ENCLOSURES



Modules		4	8	12	
<b>40 CDK RANGE</b> - <b>MODULAR WATERTIGHT ENCLOSURES AND DISTRIBUTION BOARDS</b> - <b>IP65</b>	<b>Protection class:</b> IP 65 <b>Colour:</b> RAL 7035 grey <b>Door:</b> smoked transparent <b>Walls:</b> smooth				
	<b>Code</b>	<b>GW 40 101</b>	<b>GW 40 102</b>	<b>GW 40 103</b>	
	Surface-mounting fixing brackets for enclosures and boards	GW 44 621	4	4	4
	Stylish coupling covers for conduit and trunking entry	GW 40 473	-	-	1
		GW 40 474	-	-	-
	Insulated neutral and earth terminal blocks	GW 40 401	-	1	-
		GW 40 402	-	-	1
		GW 40 404	-	-	-
	Internal horizontal dividers	GW 40 487	-	-	-
		GW 40 488	-	-	-
1-module high blank cover panels	GW 40 492	-	-	-	
	GW 40 493	-	-	-	
Cylindrical safety lock	GW 40 422	1	1	1	

40 CD RANGE

Modules		4	8	12	
<b>40 CD RANGE</b> - <b>WATERTIGHT ENCLOSURES</b> - <b>IP55</b>	<b>Protection class:</b> IP 55 <b>Colour:</b> RAL 7035 grey <b>Door:</b> smoked transparent <b>Walls:</b> with perforation centres				
	<b>Code</b>	<b>GW 40 001</b>	<b>GW 40 003</b>	<b>GW 40 005</b>	
	<b>Arranged for terminal block housing</b>			<b>GW 40 004</b>	
	<b>With terminal block</b>				
	Surface-mounting fixing brackets for enclosures and boards	GW 44 621	4	4	4
	Insulated neutral and earth terminal blocks	GW 40 401	-	1	-
GW 40 402		-	-	1 (x GW 40 005), supplied (x GW 40 004)	
Triangular key	GW 40 421	-	-	1	



# 40 CD RANGE

SURFACE-MOUNTING DISTRIBUTION BOARDS AND ENCLOSURES



	18	24 (12x2)	36 (12x3)	36 (18x2)	54 (18x3)	72 (18x4)
						
	<b>GW 40 106</b>	<b>GW 40 104</b>	<b>GW 40 105</b>	<b>GW 40 107</b>	<b>GW 40 108</b>	<b>GW 40 109</b>
	4	4	4	4	4	4
	-	1	1	-	-	-
	1	-	-	1	1	1
	-	-	-	-	-	-
	-	1	2	-	-	-
	1	-	-	2	2	2
	-	1	2	-	-	-
	-	-	-	1	2	3
	-	2	3	-	-	-
	-	-	-	2	3	4
	1	1	2	1	2	2






40 CD RANGE

	24 (12x2)	36 (18x2)
		
	<b>GW 40 007</b>	<b>GW 40 009</b>
	<b>GW 40 006</b>	<b>GW 40 008</b>
	4	4
	2 (x GW 40 009), supplied (x GW 40 006)	-
	-	2 (x GW 40 009), supplied (x GW 40 008)
	1	1






# 40 CD RANGE

SURFACE-MOUNTING DISTRIBUTION BOARDS AND ENCLOSURES



		Modules	8	12	24 (12x2)	
40 CD RANGE - PROTECTED DECORATIVE ENCLOSURES - IP40	<b>Protection class:</b> IP 40 <b>Colour:</b> RAL 9016 white <b>Door:</b> smoked transparent <b>Walls:</b> smooth					
	Code	Arranged for terminal block housing	GW 40 043	GW 40 045	GW 40 047	
		With terminal block		GW 40 044	GW 40 046	
		Surface-mounting fixing brackets for enclosures and boards	GW 44 621	4	4	4
		Insulated neutral and earth terminal blocks	GW 40 401	1	-	2 (x GW 40 047), supplied (x GW 40 046)
GW 40 402			-	1 (x GW 40 045), supplied (x GW 40 044)	-	
	Metal cylinder security lock	GW 40 422	1	1	1	

40 CD RANGE





		Modules	2	4	6	
40 CD RANGE - PROTECTED ENCLOSURES - IP40	<b>Protection class:</b> IP 40 <b>Colour:</b> RAL 7035 grey <b>Without door</b> <b>Walls:</b> with perforation centres					
	Code	Arranged for terminal block housing	GW 40 022	GW 40 023	GW 40 024	
		With terminal block				
		Surface-mounting fixing brackets for enclosures and boards	GW 44 621	4	4	4
		Insulated neutral and earth terminal blocks	GW 40 401	-	-	-
GW 40 402			-	-	-	

# 40 CD RANGE

SURFACE-MOUNTING DISTRIBUTION BOARDS AND ENCLOSURES



	36 (18x2)	54 (18x3)	72 (18x4)
			
	<b>GW 40 049</b>	<b>GW 40 051</b>	<b>GW 40 053</b>
	<b>GW 40 048</b>		
	4	4	4
	-	-	-
	2 (x GW 40 049), supplied (x GW 40 048)	2	4
	1	1	2

	8	12+1	24+2 (12x2)	36+3 (12x3)
				
	<b>GW 40 026</b>	<b>GW 40 028</b>	<b>GW 40 030</b>	<b>GW 40 032</b>
		<b>GW 40 027</b>	<b>GW 40 029</b>	<b>GW 40 031</b>
	4	4	4	4
	1	-	2 (x GW 40 030), supplied (x GW 40 029)	-
	-	1 (x GW 40 028), supplied (x GW 40 027)	-	2 (x GW 40 032), supplied (x GW 40 031)

40 CD RANGE