Product Data Sheet

GW70494P

70 RT HP Range




70 RT HP is a new range of 16A to 160A switch disconnectors in isolating material and metal, supplied in a box. Available in control and emergency versions, the range is completed by board versions for front-panel or DIN rail assembly, in 16 to 63A options, all of which can be equipped with auxiliary contacts. These devices have been designed for deliver the ultimate in reliability, functionality and performance. They offer a technologically advanced solution that simplifies installation, reduces wiring times and ensures maximum safety and robustness, even in the most demanding conditions, thanks to the use of high-performance materials.

Version	Box	**Material**	Insulation
Type	For emergency	**Rated current (A)**	125
Circuit breaker	Rotary isolator	**IP degree**	IP66/IP67/IP69
Shock resistance	IK08	**Ambient temperature**	-25 +60 °C
Lid screws (no. and type)	4 insulation	**Lockable**	YES (max. 3 locks in OFF)
Complete with	Max. 4 auxiliary contacts	**Current in AC22 (415V)**	125
Current in AC23 (415V)	125	**Cable section**	Max 70 mm²
Outer dim. LxHxD (mm)	236,5x316x178	**Electrocod**	1742


BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluited	Concentrated	Diluited	Hexane	Benzol	Acetone	Ethyl alcohol		
Resistant	Limited resistance	Resistant	Not resistant	Limited resistance	Limited resistance	Not resistant	Not resistant	Limited resistance	Resistant	Resistant

DIMENSIONAL



TECHNICAL SYMBOLOGY



IP66/IP67/IP69



IK08

STANDARDS/APPROVALS

CE

GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 21/06/2018

Data, measures, designs and pictures are shown only as informativ purposes,
and could be changed without previous notice