


Model	Code	Ø Cable [mm]	Model	Code	Pcs /pack
<b>SPP K0G</b>	<b>1731021100</b>	<b>"blind"</b>	<b>SPP K0B</b>	<b>1731023100</b>	<b>1 / 10</b>
<b>SPP K1G</b>	<b>1731021110</b>	<b>2.5/7</b>	<b>SPP K1B</b>	<b>1731023110</b>	
<b>SPP K2G</b>	<b>1731021115</b>	<b>5/10</b>	<b>SPP K2B</b>	<b>1731023115</b>	
<b>SPP K3G</b>	<b>1731021120</b>	<b>7.5/11.5</b>	<b>SPP K3B</b>	<b>1731023120</b>	
<b>SPP K4G</b>	<b>1731021125</b>	<b>10/14</b>	<b>SPP K4B</b>	<b>1731023125</b>	

## DES inserts with extended range - non split

- ▶ Extended range inserts for **non-terminated cables**
- ▶ Diameters from 2.5 to 14 mm
- ▶ "Blind" insert pierceable available
- ▶ Grey and black colours available
- ▶ UL94V0 for both colours

The SPP K inserts enable non-terminated cables to be accommodated in the DES splittable frames. Each insert has an extended range. The "blind" insert, properly pierced, enables cables from 1 to 16mm in diameter to pass through the frame.



### Technical data

**Material:** TPE

**Flammability:** self-extinguishing acc. to UL94-V0

**Temperature:** -40°C... +110°C (static)

**Features:** halogens and silicones free

### Related products

- |        |        |             |
|--------|--------|-------------|
| DES 24 | DES L5 | DES PRED    |
| DES 16 | DES L4 | DES PRED 90 |
| DES 10 | DES L3 | DES CLICK   |
| DES Q  | DES L2 |             |

