




Model	Code	Cable nr. - Ø cables min/max [mm]	Dimensions [mm]		Pcs /pack
			Cut-out	Plate	
DES-PDM Q 13G	1732014613	8 - 2.8 / 6.5 4 - 4.6 / 10.2 1 - 14.5 / 22	46 x 46	74x60	1 / 10
DES-PDM Q 17G	1732014617	10 - 2.8 / 6.5 4 - 4.6 / 10.2 2 - 6.8 / 12 1 - 8.6 / 16.2			
DES-PDM Q 25G	1732014625	25 - 2.8 / 6.5			
DES-PDM Q 13B	1732015614	8 - 2.8 / 6.5 4 - 4.6 / 10.2 1 - 14.5 / 22	46 x 46	74x60	1 / 10
DES-PDM Q 17B	1732015618	10 - 2.8 / 6.5 4 - 4.6 / 10.2 2 - 6.8 / 12 1 - 8.6 / 16.2			
DES-PDM Q 25B	1732015626	25 - 2.8 / 6.5			

## Cable entry plates with internal frame

- ▶ For several number of non-terminated cables in a limited space
- ▶ High retaining force thanks to the double membrane
- ▶ Cost efficient solution
- ▶ High IP grade (IP65-66)



Double membrane



The DES-PDM Q is an innovative alternative to standard cable glands on electrical, electronic and telecommunication cabinets and equipment.

The cable is pushed through the front membrane, whilst the second membrane increases the strain relief and liquid resistance.

## Technical data

**Material:** TPE

**Flammability:** self-extinguishing acc. to UL94-V0

**Temperature:** -40°C... +105°C (static)

**Features:** halogens and silicones free

## Related products

Hydraulic punch driver HY360

## Dimensions [mm]

