



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

## Closure cap for Socket TH389U/TH629U

Code: **GDB069700**



Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

### GENERAL DESCRIPTION

<b>Type of installation</b>	Sealing cap
<b>Product configuration</b>	Sealing cap
<b>Locking mechanism</b>	Push Pull
<b>Colour</b>	Black

## ENVIRONMENT CONDITIONS

IP rating	IP66
Salt Mist	Salt mist test : EN60068-2-11:2000
Ambient temperature MIN/MAX (According to EN61984/EN60998)	-40°C/+125°C

## MATERIALS



Exterior body	PA66 UL94 V2 Silicone
Material property	Halogen Free

## COMMERCIAL DATA

Packing method	Bulk packed ( OEM )
Type of packaging	Box
Pieces/box (pcs)	200
Weight per Piece (gr)	5.46
Custom tariff number	85389099
Country of origin	ITALY


## APPROVALS

### REACH/RoHS Approvals:

File	Type	Size
 <a href="#">REACH.pdf</a>	PDF	105.87 KB
 <a href="#">RoHS Compliance.pdf</a>	PDF	84.57 KB

## DRAWINGS

### Drawings:

File	Type	Size
 <a href="#">6DB069700.pdf</a>	PDF	313.76 KB