



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

KIT Junction Connector "T" 3p Screw D6-13.5 IP68

Code: **THR.390.S3T**



Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

GENERAL INFORMATION

Type of installation	Joint connector (re-usable/re-accessible)
Product configuration	Junction connector
Colour	Black (Plastic components) - Techno green (Rubber components)
Overall dimensions (mm)	Ø 32.0 x 97.0 x 77.0

ELECTRIC DATA

No. connected cables	3
Circuit wiring diagram	Power/Signal
Current rating (AC/DC)	32A
Voltage rating (AC/DC)	450V AC
No. poles	3
Marking	L-N-E
Terminations	Screw
Terminations Thread/Tightening torque	M3 - 0.8 Nm

CONNECTION DATA

**to use the 6.0 mm outer cable diameter it is necessary to use the reduction of nut already contained in the kit*

Multi-stranded conductor cross-section without ferrule MIN (mm ²)	0.50
Multi-stranded conductor cross-section without ferrule MAX (mm ²)	1.50
	<i>*Cable sections up to 4 mm² accepted according to indicated electrical and technical parameters</i>
Solid conductor cross-section MIN (mm ²)	0.50
Solid conductor cross-section MAX (mm ²)	1.50
Conductor stripping length (mm)	8.00
Main cable sheath stripping length (mm)	50.00
Branch cable sheath stripping length (mm)	30.00
Reccomended types of cable	H05xxx/H07xxx
Cable diameter MIN (mm)	6.00
Cable diameter MAX (mm)	13.50
Tightening torque of cable gland-connector	2.5 Nm
Tightening torque of nut-cable gland	2.5 Nm

ENVIRONMENT CONDITIONS

IP rating	IP68
	<i>*IP68 (20m/1h)</i>
IK rating	IK07
Salt Mist	Salt mist test : EN60068-2-11:2000
T marking	T 125°C
Proof Tracking Index (PTI)	PTI 250

MATERIALS

Exterior body	PA66 GF UL94 V0
Connector	PA66 GF UL94 V0
Cable gland	PA66 UL94 V2
O Rings	Silicone
Gaskets	TPE
Material property	Halogen Free
Contacts	Brass
Contact screws	Steel

PRODUCT COMPLIANCES

IEC Approvals	EN 60998-1:2004
---------------	-----------------

Item Code: THR.390.S3T

Description: Circular mini-junction connector 3 ways type "T"

Item THB.390.A1A – THB.020.A1A

Features / Property






Description Circular mini-junction connector 3 ways type "T"

IP protection: IP68

Contact marking: L – N – E

Type of packaging: single packed unit, not assembled. Installation Sheet included in the kit.

Item	Description	Quantity
 6000087LF	Cable reductions 6-7 mm	3
 600013700	Closure caps	1
 6000337BC	Fixing tool	1