Standard 4 Pole AC Contactors (Power Poles)

AC3 ❷		AC1 ❷	POWER POLES		PART NUMBER	MAX AUX ❸		DIMENSIONS			TRADE PRICE
kW	Amp	Amp	N/O	N/C		N/O	N/C	High	Wide	Deep	
4 N/O Power Poles											
4	9	30	4	-	GH15BN-4-00- ❶ AC	6	4	80	45	85	
7.5	16	40			GH15DN-4-00- ❶ AC						
15	32	50			GH15FN-4-00- ❶ AC	7	5	114	60	105	
20	40	63			GH15GN-4-00- ❶ AC						
22	50	80			GH15HN-4-00- ❶ AC			114	79	109	
30	63	100			GH15JN-4-00- ❶ AC						
45	95	135			GH15LN-4-00 -❶ AC			142	105	130	
55	115	200			GH15MN-4-00- ❶ AC	6	4	170	147	162	
75	150	250			GH15NN-4-00- ❶ AC						
90	175	300			GH15PN-4-00- ❶ AC						
110	210	350			GH15RN-4-00- ❶ AC			200	193	208	
132	260	450			GH15SN-4-00- ❶ AC						
160	315	600			GH15TN-4-00- ❶ AC						
4 N/C Power Poles											
4	9	30	-	4	GH15BN-04-00- ❶ AC	6	4	80	45	85	
18.5	40	63			GH15GN-04-00- ❶ AC	7	5	114	79	109	
45	95	135			GH15LN-04-00- ❶ AC			142	105	130	
2NO / 2NC Power Poles											
4	9	30	2	2	GH15BN-22-00- ❶ AC	6	4	80	45	85	
18.5	40	63			GH15GN-22-00- ❶ AC	7	5	114	79	109	
45	95	135			GH15LN-22-00- ❶ AC			142	105	130	

Notes:
❶ Complete the Part Number with Coil Voltage. *Standard voltages are: -AC: 24,48,110,230,400V -DC: 24,48,110,220V (POA)*
❷ Rated at 40°C.
❸ Maximum number of NO or NC auxiliary contacts that can be fitted to contactor.
- 4th add-on neutral switching poles are available for standard 3-pole contactors sizes GH55B to GH78, on request.

