




Watertight enclosure for emergency use and special applications with rail DIN. It is available in red RAL 3000 or grey RAL7035 colours. Thanks to the emergency hammer, available as an accessory, sealable mask and halogen free materials are ideally suited for applications in areas open to public.

| | | | |
|-----------------------|--|---------------------------|--|
| Rated current (A) | 125 | Insulation class | II |
| Colour | Grey RAL 7035 | Outer dim. LxHxD (mm) | 108x180x100 |
| IP degree | IP55 | Installation | Wall mounting |
| Material | Technopolymer | Shock resistance | IK08 |
| Rated voltage (V) | 400 | Glow Wire Test | 650 °C |
| Operating temperature | -25 +60 °C | Type of material | Halogen-free in compliance with EN 60754-2 |
| Electrocod | 0321 | Thermo-pressure with ball | 70 °C |
| Standard | EN 60670-1 (CEI 23-48) IEC60670-24 CEI 23-49 | Insulation voltage | 750 V |
| Dispersible power (W) | 12 | No. of modules EN 50022 | 4 |

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

| Saline solution | Acids | | Bases | | Solvents | | | | Mineral oil | UV rays |
|-----------------|---------------|-----------|--------------|-----------|--------------------|---------------|---------------|--------------------|--------------------|--------------------|
| | Concentrated | Diluted | Concentrated | Diluted | Hexane | Benzol | Acetone | Ethyl alcohol | | |
| Resistant | Not resistant | Resistant | Resistant | Resistant | Limited resistance | Not resistant | Not resistant | Limited resistance | Limited resistance | Limited resistance |

DIMENSIONAL



TECHNICAL SYMBOLOGY



STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 30/04/2018

Data, measures, designs and pictures are shown only as
informativ purposes,
and could be changed without previous notice